

Recommended Cleaning & Care

BUZIL-WERK Wagner GmbH & Co. KG

ARTIFICIAL RESIN SURFACING



Artificial resin coverings consist of artificial resin (polyurethane, epoxide and polyester resins) and fillers, e.g. quartz dust, quartz sand, corundum and glass fibres. Oxide pigments are used for colouration. Synthetic resin surfacing has no joints, or it is cast or smoothed using expansion joints. Smooth and rough surfaces are used for these coverings. Although they are generally resistant to chemicals, they are sensitive to aggressive organic solvents.

CLEANING

DEEP CLEANING

	Dirt	Treatment	Cleaning device
Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.	ORGANIC/INORGANIC CONTAMINATION e.g. heavy oil, grease and protein deposits or foodstuff residue e.g. coffee, red wine etc. can be removed using Indumaster® Strong IR 45. <i>PLEASE NOTE: Check the floor covering for colour-fastness before cleaning!</i>	Apply the cleaning solution evenly over the floor, and leave it to work for approximately 10 to 15 minutes.	
		Deep clean the covering using a single-disc machine and a brush, or a cleaning machine with a brush.	
		Pick up the loosened dirt using a wet vacuum cleaner, and rinse with water.	

INTENSIVE CLEANING

	Dirt	Treatment	Cleaning device
Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.	HEAVIER DIRT THAT IS ALKALINE-SOLUBLE e.g. heavy oil, grease and protein deposits or foodstuff residue e.g. coffee, red wine etc. can be removed by intensive cleaning using Indumaster Step IR 16 or Perfekt G 440 using a two-stage wet wiping method, or mechanically.	Apply the cleaning solution evenly over the floor, and leave it to work for a short time.	
		Clean using a single-disc machine and an appropriate brush.	
		Pick up the loosened dirt using a wet vacuum cleaner, and rinse with water.	

Recommended Cleaning & Care

BUZIL-WERK Wagner GmbH & Co. KG

CONTINUED: CLEANING ARTIFICIAL RESIN SURFACING

SPECIAL CLEANING

	Dirt	Treatment	Cleaning device
<p>Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.</p>	<p>RUBBER ABRASION</p> <p>The solvent-containing Indumaster® Forte IR 42 cleaner is particularly well-suited to removing rubber abrasion when diluted 1:1.</p>	<p>Spray the product onto targeted areas.</p>	
		<p>Scrub the covering using a single-disc machine and a suitable pad.</p>	
		<p>Pick up the loosened dirt using a wet vacuum cleaner, and rinse with water. <i>PLEASE NOTE: Perform a material compatibility test before use!</i></p>	

DAILY ROUTINE CLEANING

	Dirt	Treatment	Cleaning device
<p>Microfibre-based flat mops should be used to achieve optimum cleaning results.</p>	<p>ORGANIC/INORGANIC CONTAMINATION</p> <p>e.g. heavy oil, grease and protein deposits or foodstuff residue e.g. coffee, red wine etc.</p> <p>Products without a care element, such as Corridor® PUR Clean S 766 floor cleaner and Buz® Wipe G 270 gloss cleaners and are well-suited to daily routine cleaning.</p> <p>The Maradin HC 43 intensive cleaner is well-suited to daily routine cleaning of heavier dirt.</p>	<p>Manual floor treatment</p>	

CARE

INITIAL TREATMENT

In order to retain the slip resistance and appearance of these floor coverings, they must not be coated, impregnated or subject to initial treatment.