

Recommended Cleaning & Care

BUZIL-WERK Wagner GmbH & Co. KG

LINOLEUM FLOOR COVERINGS, COATED



Linoleum consists of natural materials. To produce it, linseed oil is blended with natural resins, wood and cork dust, inorganic fillers, and colour pigments. This mass is put under pressure and pressed onto a jute fabric. Linoleum is sensitive to alkaline cleaners and deep cleaners with a pH-value greater than 10, abrasive pads, and brushes. There are linoleum floors that exhibit discolouration or odours when treated just with clean water, or become so porous after deep cleaning that a drying time of at least 12-24 hours is necessary before the first coating. Residual moisture in the covering would result in the coating "powdering" or "loosening".

© Forbo Flooring GmbH

CLEANING

DEEP CLEANING

	Dirt	Treatment	Cleaning device
Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.	RESIDUE FROM CARE PRODUCTS	Apply the cleaning solution evenly over the floor, and leave it to work for approximately 10 to 15 minutes. <i>PLEASE NOTE: Do not allow the cleaning solution to dry.</i>	
	in the form of coatings and care products can be removed using Corridor® Unic Ultra S 707, Corridor® Power Stripper S 708 or Planta® Multi Stripper P 321.	Deep clean the covering using a single-disc machine and a blue pad.	
		Pick up the loosened dirt using a wet vacuum cleaner, and rinse with water. <i>PLEASE NOTE: Leave the floor to dry completely before applying a coating (up to 24 hours).</i>	

INTENSIVE CLEANING

	Dirt	Treatment	Cleaning device
Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.	HEAVIER DIRT THAT IS ALKALINE-SOLUBLE	Apply the cleaning solution evenly over the floor, and leave it to work for a short time.	
	like protein, oil and grease or foodstuff residue e.g. coffee, red wine etc. can be removed by intensive cleaning using Corridor® PUR Clean S 766 using a two-stage wet mopping method, or mechanically.	Clean the covering using a single-disc machine and a red pad.	
		Pick up the loosened dirt using a wet vacuum cleaner, and rinse with water.	

Recommended Cleaning & Care

BUZIL-WERK Wagner GmbH & Co. KG

CONTINUED: CLEANING LINOLEUM FLOOR COVERINGS

DAILY ROUTINE CLEANING

	Dirt	Treatment	Cleaning device
Microfibre cloths or pads must always be used in order to achieve a satisfactory cleaning result.	ORGANIC/INORGANIC CONTAMINATION like protein, oil and grease or foodstuff residue e.g. coffee, red wine etc. Products with a care element, such as the Corridor® Daily S 780, Corridor Cibreeze S790 with odour blocker and Planta® Clean P315 wipe care products are well-suited to daily routine cleaning.	Manual floor treatment	
	INFECTION PREVENTION	The Buzil Budenat® portfolio surface disinfectant is ideal for defined areas (see Disinfectants).	

CARE

PRIMING

Care	Treatment	Cleaning device
UV radiation, mechanical impacts and frequent deep cleaning damage the linoleum covering (linseed oils and natural resins are released). Linoleum, a natural product, becomes porous, meaning dirt can permeate its deeper layers; this dirt is then very difficult to remove using only daily routine cleaning. The use of a primer is recommended/necessary. PLEASE NOTE: Corridor® Basic S 720 is not dissolved during later deep cleaning, and is therefore a permanent primer that only needs to be renewed after some years.	The application of Corridor® Basic S 720 pore filler/primer in 1-2 layers, depending on the condition of the covering, is recommended.	

Recommended Cleaning & Care

BUZIL-WERK Wagner GmbH & Co. KG

CONTINUED: CARING FOR LINOLEUM FLOOR COVERINGS

INITIAL TREATMENT

Care	Treatment	Cleaning device
<p>These floor coverings can be used with the extremely durable Corridor® Jewel S 741 high-performance dispersion, offering protection against mechanical damage and improving the appearance of the floor.</p> <p>Alternatively, products such as Corridor® Glorin S 734, Planta® Multi Gloss P 320 (gloss), Corridor® Matt S 737 (silky matt) and Emulsion Corridor® Complete S 732 (gloss) are also well-suited for this purpose.</p>	<p>Apply the dispersion undiluted onto the dry, deep-cleaned floor in two thin layers, leaving each individual layer to dry completely.</p>	
	<p>Polishing is not required.</p>	

COATING REPAIR

Care	Treatment	Cleaning device
<p>Pick up loose dirt, and remove any mortar, plaster residue, and colour stains manually using a scraper.</p>	<p>Spray the Maradin HC 43 intensive cleaner onto the surface at the recommended dosage, working on a section at a time.</p>	
	<p>Clean the area using a single-disc machine and a red pad.</p>	
	<p><i>Replace the pad regularly when doing so.</i></p>	
	<p>Then wipe the floor covering with water; further rinsing and neutralisation are not necessary.</p>	
	<p>Spray Corridor® Spray S 770 (undiluted) onto the clean surface, working on a section at a time.</p>	
	<p>Use a high-speed machine and a polishing pad to achieve a high gloss floor finish.</p>	